

General Purpose, Flame Retardant Polyolefin Tubing



PRODUCTS DESCRIPTION		產品描述	
MATERIAL	Polyolefin (PE)	材 質	環保PE製成
COLOR	Black, Red, Blue, Yellow, White, Green	顏 色	黑色、紅色、藍色、黃色、白色、綠色
TEMPERATURE RANGE	Operating temperature : -55°C ~ 125°C Minimum shrink temperature : 70°C Minimum fully recovery temperature : 110°C	操作溫度	操作溫度 : -55°C ~ 125°C 最低收縮溫度 : 70°C 最低完全收縮溫度 : 110°C
VOLTAGE RANGE	600V	耐電壓值	600V
FLAMMABILITY	VW-1	耐燃等級	VW-1
General purpose tubing for military and commercial applications such as electrical insulation and protecting in-line components, disconnect terminals, and splices. Used for jacketing wire bundles and light-duty harness and identifying or color-codes wires, cables, terminals, and components.		特 點	本產品具有環保、柔軟、阻燃..等特性,可廣泛的應用於電線連接、焊點保護、電線端部以及線束即電子元件的防護和絕緣處理,另外還常被用於顏色標識

PRODUCTS SPECIFICATION

ITEM NO.	Size (mm)	AS SUPPLIED 收縮前 (MM)		AFTER RECOVERY 收縮後 (MM)		PACKAGE (M/S POOL)
		內徑 (max.)	壁厚 (min.)	內徑 (max.)	壁厚 (min.)	
G5-0.8	∅0.8	1.0 ± 0.2	0.15 ± 0.05	0.4	0.25 ± 0.05	200
G5-1	∅1.0	1.5 ± 0.3	0.20 ± 0.05	0.6	0.33 ± 0.05	200
G5-1.5	∅1.5	2.0 ± 0.3	0.20 ± 0.05	0.75	0.36 ± 0.05	200
G5-2	∅2.0	2.5 ± 0.3	0.20 ± 0.05	1.0	0.44 ± 0.05	200
G5-2.5	∅2.5	3.0 ± 0.3	0.25 ± 0.05	1.25	0.44 ± 0.05	200
G5-3	∅3.0	3.5 ± 0.3	0.25 ± 0.05	1.5	0.44 ± 0.05	200
G5-3.5	∅3.5	4.0 ± 0.3	0.25 ± 0.05	1.75	0.44 ± 0.05	200
G5-4	∅4.0	4.5 ± 0.3	0.25 ± 0.05	2.0	0.44 ± 0.05	200
G5-4.5	∅4.5	5.0 ± 0.3	0.25 ± 0.05	2.25	0.44 ± 0.08	100
G5-5	∅5.0	5.5 ± 0.3	0.25 ± 0.05	2.5	0.56 ± 0.08	100
G5-6	∅6.0	6.5 ± 0.3	0.28 ± 0.05	3.0	0.56 ± 0.08	100
G5-7	∅7.0	7.6 ± 0.3	0.30 ± 0.06	3.5	0.56 ± 0.08	100
G5-8	∅8.0	8.6 ± 0.3	0.30 ± 0.06	4.0	0.56 ± 0.08	100
G5-9	∅9.0	9.6 ± 0.3	0.30 ± 0.06	4.5	0.56 ± 0.08	100
G5-10	∅10.0	10.7 ± 0.4	0.30 ± 0.06	5.0	0.56 ± 0.08	100
G5-11	∅11.0	11.7 ± 0.4	0.30 ± 0.06	5.5	0.56 ± 0.08	100
G5-12	∅12.0	12.7 ± 0.4	0.30 ± 0.06	6.0	0.56 ± 0.08	100
G5-13	∅13.0	13.7 ± 0.4	0.35 ± 0.07	6.5	0.69 ± 0.08	100
G5-14	∅14.0	14.7±0.4	0.35 ± 0.07	7.0	0.69 ± 0.08	100
G5-15	∅15.0	15.7±0.5	0.35 ± 0.07	7.5	0.69 ± 0.08	100
G5-16	∅16.0	16.7 ± 0.5	0.35 ± 0.07	8.0	0.69 ± 0.08	100
G5-17	∅17.0	17.5 ± 0.6	0.35 ± 0.12	8.5	0.77 ± 0.08	100
G5-18	∅18.0	19.0 ± 0.5	0.40 ± 0.10	9.0	0.77 ± 0.15	100
G5-20	∅20.0	21.0 ± 0.5	0.40 ± 0.10	10.0	0.77 ± 0.15	100
G5-22	∅22.0	23.0 ± 0.5	0.40 ± 0.10	11.0	0.77 ± 0.15	100
G5-25	∅25.0	26.0 ± 1.0	0.45 ± 0.10	12.5	0.87 ± 0.15	50
G5-28	∅28.0	29.0 ± 1.0	0.45 ± 0.10	14.0	0.87 ± 0.15	50
G5-30	∅30.0	31.5 ± 1.0	0.45 ± 0.10	15.0	0.87 ± 0.15	50
G5-35	∅35.0	37.0 ± 1.0	0.50 ± 0.10	17.5	0.97 ± 0.15	50
G5-40	∅40.0	40.5 ± 1.0	0.50 ± 0.10	20.0	0.97 ± 0.15	50
G5-45	∅45.0	46.0 ± 1.0	0.50 ± 0.10	22.5	0.97 ± 0.15	25
G5-50	∅50.0	50.5 ± 1.0	0.50 ± 0.10	25.0	0.97 ± 0.15	25
G5-60	∅60.0	60.0 ± 3.0	0.80 ± 0.20	30.0	1.30 ± 0.20	25
G5-70	∅70.0	70.0 ± 3.0	0.80 ± 0.20	35.0	1.50 ± 0.20	25
G5-80	∅80.0	80.0 ± 3.0	0.80 ± 0.30	40.0	1.50 ± 0.30	25
G5-90	∅90.0	90.0 ± 4.0	0.80 ± 0.30	45.0	1.50 ± 0.30	25
G5-100	∅100	100.0 ± 4.0	0.80 ± 0.30	50.0	1.50 ± 0.30	25
G5-120	∅120	120.0 ± 4.0	0.80 ± 0.30	60.0	1.50 ± 0.30	15
G5-150	∅150	150.0 ± 4.0	0.80 ± 0.30	75.0	1.50 ± 0.30	15
G5-180	∅180	180.0 ± 4.0	0.80 ± 0.30	90.0	1.50 ± 0.30	15